

SDA SELF-DRIVEN PLASTERBOARD PLUG



Nylon body



Metal body

FEATURES

- Self-drilling without the use of drilling machine.
- Fasten up to 16mm plasterboard.
- Accept ordinary wood screws with any head profiles.
- Nylon plug flush to wall without any tearing or bubbling.
- Versatile as nylon plug is easy to set or remove if needed.

APPLICATIONS

- Lightweighted M&E fixtures on wall.
- Decorative fixture, picture and poster frames.
- Tie-back for shelving, wardrobe and cabinets.
- Fixing of curtain track, skirting and light architectural finishes.


RANGE OF LOADING

Hanging load up to 35kgs.

BASE MATERIALS



Plasterboard



Dry partition

▶ ORDERING DETAILS

SDA SELF-DRIVEN PLASTERBOARD PLUG (NYLON BODY)

ANCHOR SIZE	MAX. PLASTERBOARD THICKNESS, t_{wall} (mm)	PACKING CONTENT (PCs.)	PRODUCT PART NO.
15 x 33	16	100	SDA533N



SDA SELF-DRIVEN PLASTERBOARD PLUG (METAL BODY)

ANCHOR SIZE	MAX. PLASTERBOARD THICKNESS, t_{wall} (mm)	PACKING CONTENT (PCs.)	PRODUCT PART NO.
15 x 28	16	100	SDA528M



▶ INSTALLATION PERIMETER & LOADING DATA

ANCHOR SIZE	RECOMMENDED SCREW DIAMETER (mm) d_{scw}	MINIMUM SCREW LENGTH (mm)	FIXTURE HOLE DIAMETER (mm) d_{fix}	RECOMMENDED HANGING LOAD IN VARIOUS PLASTERBOARD THICKNESS' [kN]		
				9mm	12-13mm	15-16mm
15 x 33	4.0 ~ 4.5	30	5.0 ~ 5.5	0.30	0.34	0.36
15 x 28	4.0 ~ 4.5	30	5.0 ~ 5.5	0.15	0.18	0.23



¹ Safety factor of 4.0 is recommended.

▶ INSTALLATION PROCEDURE

